



Efficient printing and unrivalled textile print quality, now with orange and violet inks.

Epson new powerhouses, SureColor F6430/F6430H, are setting fresh benchmarks in textile printers with their reliable and superior print quality. Offering a high-performance solution for small to mid-sized textile production companies, these 44" digital dye sublimation printers are equipped with an integrated ink system and the all-new PrecisionCore MicroTFP Printhead. With the addition of orange and violet inks, the SC-F6430H raises the bar with its 6-colour printing, delivering fluorescent brightness and unique colours for specific printing needs.









Reliable & High Productivity

Equipped with the all-new 1.33-inch PrecisionCore MicroTFP printhead, printing speeds are improved by approximately 20%*.

Integrated Ink System

Minimise downtime with the improved 1.6L ink capacity along with easy and user-friendly machine operation and maintenance. Ink life after installation has been improved up to one year from just 25 days.

Improved Colour Options

Expand business opportunities with SC-F6430H's improved colour set options which are fluorescent yellow and fluorescent pink, light cyan and light magenta, and orange and violet.

MODEL NUMBER	SC-F6430	SC-F6430H	PRINTER DIMENSION
PRINT	Dun sining Court Indiat To should an		SC-F6430/F6430H
Technology 1 Technology 2	PrecisionCore Inkjet Technology Variable-Sized Droplet Technology		Without Take Up Reel
Printhead	Variable-Sized Droplet Technology PrecisionCore MicroTFP Printhead		
Nozzle Configuration	The number of nozzles:	The number of nozzles:	
1 102210 Seringaration	3,200 nozzles	2,400 nozzles	D/200
	CMYHDK:	CMYHDKLcLm: 2,400 nozzles (400 x 6 colours)	1,128 mm
	3,200 nozzles	CMYHDKFpFy: 2,400 nozzles (400 x 6 colours)	
	(800 x 4 colours)	CMYHDKOrV: 2,400 nozzles (400 x 6 colours)	
Maximum Resolution	600 x 1,200 dpi		
Minimum Ink Droplet Volume	3.6pl		1.608 mm
Maximum Print Speed	78.3 m²/h	38.8 m²/h	1,006 11111
Margin (Roll Paper)	3~25 mm (Right/Left) / 5~35 m		
INK	<u> </u>		With Take Up Reel
Ink Types	Dye Sublimation Transfer Ink		100 mars 100 mm
Ink Brand Name	UltraChrome DS Ink	UltraChrome DS 6 Ink	1000 E
Colours	Cyan, Magenta, Yellow, High De		
	N/A	Light Cyan, Light Magenta,	1,128 mm
		Fluorescent Yellow, Fluorescent Pink,	
		Orange, Violet	
Ink Capacity	1.6L	<u> </u>	
Ink Case	Ink Supply Unit		916 mm
MEDIA HANDLING			-,
Paper Path	Roll (Single Roll)		
Paper Feed Method	Friction Feed		UltraChrome DS Inks
Paper Width (Roll)	254 mm to 1,118 mm (10" to 44")		Cyan C13T53Q200
Paper Thickness (Roll)	Up to 0.5 mm	- ,	Magenta C13T53Q300
CONTROL PANEL			Yellow C13T53Q400
Colour/Size	4.3" Colour LCD Touch Panel		High Density Black C13T53Q900
CONNECTIVITY	4.0 Colour LOB Todoll 1 dilor		UltraChrome DS 6 Inks
Interfaces	Super Speed USB, 100BASE-TX/1000BASE-T		Light Cyan C13T53Q500
Printer Language	ESC/P raster		Light Magenta C13T53Q600
Memory	1 GB		Fluorescent Pink C13T53Q800
ENVIRONMENT	1 48		Fluorescent Yellow C13T53Q700
CHARACTERISTICS			Orange C13T53QA00
Temperature (°C)	Operating: 10 °C – 35 °C		Violet C13T53QD00
Temperature (G)	Storage: -20 °C - 40 °C		
Humidity	Operating: 20 – 80% (No Condensation)		Options & Consumables
DIMENSIONS	Operating: 20 - 00 /0 (NO Condensation)		Auto Take-up Reel Unit C12C934671
Printer (W x D x H)	With Take Up Reel: 1,608 x 916 mm x 1,128 mm Without Take Up Reel: 1,608 x 745 mm x 1,128 mm		Roll Adapter C12C934701 Maintenance Kit C13S210063
Filliter (W X D X II)			Head Maintenance Kit C13S400145
WEIGHT	_ viillout take up heel. 1,000 x	743 11111 X 1,126 11111	Waste Ink Bottle C13T724000
	Approx 100 kg	LApprox 140 kg	Auto Cutter Spare Blade C13S902006
With Take Up Reel:	Approx. 133 kg	Approx. 140 kg	
Without Take Up Reel: ELECTRICAL SPECIFICATION	Approx. 120 kg	Approx. 127 kg	*Bundled for SC-F6430H.
		200 AC 400\A	
Voltage	AC 220 – 240V (withstand volta	ge AC 400V)	
Frequency Rower Consumption	50/60 Hz		@0000 Faran Ciananan Dia Lid All Diabia Danas d
Power Consumption	Operating: Approx. 80W		©2022 Epson Singapore Pte Ltd. All Rights Reserved Reproduction in part or in whole, without the written
	Ready: Approx. 36W		permission from Epson, is strictly prohibited.
	Sleep: Approx. 19W	0144	EPSON and EXCEED YOUR VISION are registered
	Power Off (Standby): Approx. 0	.3W	trademarks of Seiko Epson Corporation.
ACOUSTIC NOISE LEVEL			All other product names and other company names
Sound Pressure Level - db(A)	53.5 db		used herein are for identification purposes only and are the trademarks or registered trademarks of their
Sound Power Level - B(A)	7.0 B		respective owners.
UTILITY SOFTWARE			Epson disclaims any and all rights in those marks.
Bundled in CD	Epson Software Updater, Epson Net Print, Epson Net Config SE		Projected images shown herein are simulations. The actual product design and contents may vary.
Web Delivery	Epson Edge Print Pro, Epson Edge Colour, Epson Device Admin		Specifications are subject to change without notice ar
CERTIFICATIONS			may vary between countries. Please check with local
Safety	USA and Canada (NRTL Certified), EU (Low Voltage Directive),		Epson offices for more information.
	Custom Union (Russia, Belarus, Kazakhstan) (EAC),		
	Morocco, Ukraine, India, Argentina (S-mark), Mexico (NOM), UK (UKCA),		Dealer's Stamp
	Germany (GS), Singapore, Cambodia		
WHAT'S IN THE BOX	Main unit, Stand, Waste ink bottle, Roll adapter, Epson Edge Print Pro DVD,		
	Software CD, Paper manual and instructions, Warranty sheet, AC cable,		
	Maintenance tools, Auto take-u	p reel unit (standard bundle only for F6430H)	
			Information correct at time of printing.
			Printed December 2022

PRINT

Headquarter (India): DCC Print Vision LLP,

802, Kamla Executive Park, Opp. Vazir Glass Work, Off. M.V. Road, J.B. Nagar, Andheri (East), Mumbai- 400 059, India. Tel.: +91 022 4085 5000

marketing@groupdcc.com









+91 9930 200 400