BIGGER AND BETTER. REVOLUTIONISE TEXTILE PRINTING.

SURECOLOR SC-F10030/F10030H



Featured printer is F10030H

PRODUCE LARGER PIECES OF TEXTILES WITH EPSON'S FIRST 76-INCH LARGE FORMAT TEXTILE PRINTER

Introducing Epson's SureColor SC-F10030/F10030H dye sublimation textile printer, where high efficiency, speed and reliability are central to the success of businesses. With new PrecisionCore Micro TFP printheads and an integrated dryer, greater productivity is achieved. Enjoy top-notch print quality as Precision Dot Technology leverages on optimised, new technologies to deliver astounding prints. Built to reduce downtime, a self-repair function and Epson Cloud Solution PORT feature allow users to easily replace specific components on their own for easy and seamless printer fleet management.



IT'S IN THE DETAILS.





EPSON

A MULTITUDE OF BENEFITS AWAIT

The textile industry is ever-changing and the ability to manufacture unique printed textiles on a short production run is quickly becoming a business advantage. From delivering unparalled productivity, to producing nothing less than spectacular print quality, Epson's SC-F10030/F10030H helps evolve and advance your business, taking it to the next level.

The Epson SC-F10030 comes with 4 standard colours: Cyan (C), Magenta (M), Yellow (Y) and Black (K). On the other hand, the SC-F10030H comes with 2 additional ink options for a greater print vibrancy and an expanded print application. You may choose either the Fluorescent Yellow and Fluorescent Pink (FY/FP) configuration, or the Light Cyan and Light Magenta (Lc/Lm) configuration.





ENHANCED LEVEL OF PRODUCTIVITY

When it comes to textile printing, the ability for greater quality output in the shortest amount of time is integral, especially in high volume environments.

NEW PRECISIONCORE MICRO TFP PRINTHEADS

PrecisionCore represents Epson's TFP technology, created by merging advanced key component technologies and high-precision MEMS fabrication processes. Epson's SC-F10030 integrates **four** new 4.7-inch bandwidth PrecisionCore Micro TFP Printheads that allows for a larger printing area and a maximum print speed of 255 sqm/h. On the other hand, the SC-F10030H comes with **six** printheads with a maximum print speed of 246sqm/h. With a total of 3200 nozzles per head and a head resolution of 600dpi, delivering minute detail at incredible speed with unbeatable image quality is made possible.




NEW AND IMPROVED INTEGRATED DRYER

Epson's SC-F10030/F10030H integrates a new dryer that empowers high-speed printing at a maximum temperature of 110°C. With understanding that unwanted ink transfer and wrinkling are common issues with regards to textile printing, the new dryer is designed to eliminate these worries. Paper surface temperature is controlled effectively by heating both frontside (heater with fan) and backside (heater) of the media.

STEP AND REPEAT ON PRINTER

Say goodbye to the hassle of data spooling from your PC as Epson's SC-F10030/F10030H possesses the ability to perform step and repeat print independently. By simply selecting this function and setting the print size on a RIP software, users can now reduce file transfer time from PC to printer and enjoy step and repeat print effortlessly.






EXCELLENT AND INCREDIBLE PRINT QUALITY

Heavily reliant on visual aspects, print quality plays an important role when it comes to attracting and garnering attention from audiences.



EPSON PRECISION DOT TECHNOLOGY

Epson's Precision Dot Technology consist of three different dedicated technologies, namely Micro Weave, Lookup Table (LUT) and Halftone. By optimising the Micro Weave and LUT technology, as well as developing a new Halftone – Multi-layer Halftone, Epson's SC-F10030/F10030H realises higher printing robustness against dot placement error. When these three new technologies are harmonised, amazing image quality with reduced graininess and branding is achieved.



ADVANCED AUTO TENSION CONTROL

High paper feeding accuracy contributes to high print quality. Epson's SC-F10030/F10030H advanced auto tension control function enables accurate and stable media feeding across a variety of media. The media feed motor and roll drive motor synchronises to control paper feed accurately and stably. In this way, any negative effects caused by variance in media weight, roll core shape, diameter, tackiness and take-up reel operation status is reduced. Both paper feeding and printhead (dot placement and density) adjustments are available to users.

AUTO ADJUSTMENT CAPABILITY



HIGH RELIABILITY AND UPTIME MAXIMISATION

Technical malfunctions and troubleshooting pose as common concerns. Designed for reliability, Epson's SC-F10030/F10030H gives users greater peace of mind. In the unlikely event of technical difficulties, repairing is made easy and intuitive, enabling users to solve the issue themselves for increased uptime.



BULK INK SUPPLY SYSTEM

Bulk ink supply system with 10L ink cartridges and hot swap function empowers continuous operation. Should an ink cartridge run out during printing, Epson's SC-F10030/F10030H automatically switches and activates another ink cartridge for uninterrupted printing. The finished ink cartridge can be easily replaced with a new one, all while the printer continues to print using the switched cartridge.





USER SELF-REPAIR FUNCTION

With Epson's first ever User Self-Repair function, specific parts such as the printhead and anti-drying cap can be replaced by users themselves, resulting in faster printer recovery and minimisation of downtime in comparison to waiting for service. The User Self-Repair function is supported by 3 components - Easy self-replaceable parts, Printer Diagnosis System and Epson's Remote Monitoring System.

EPSON CLOUD SOLUTION PORT

Epson Cloud Solution PORT is a cloud-based solution for Epson end users. This software provides users with the status of the connected printer and alerts for troubleshooting if required. The Production Monitor allows users to visualise printer operational status anytime, anywhere, from their PC or smart devices. In this way, productivity improves as users can identify the most urgent actions required and correct the issue efficiently with minimal disruption to the print run.





SPECIFICATIONS		
Product Name	SC-F10030	SC-F10030H
SKU Number	C11CF84403	C11CF83403
Print	Duncinian Cove Intrint Technology	
Fechnology 1 Fechnology 2	PrecisionCore Inkjet Technology Variable-Sized Droplet Technology	
Printhead	PrecisionCore Micro TFP Printhead	
	12,800 nozzles	19,200 nozzles
Nozzle Confi guration	CMYK: 12,800 nozzles	CMYKLcLm: 19,200 nozzles
	(3,200 nozzles x 4 colours)	(3,200 nozzles x 6 colours)
	(0,200 11022100 % 1 0010410)	CMYKFpFy: 19,200 nozzles
		(3,200 nozzles x 6 colours)
Maximum Resolution	1,200 x 1,200 dpi	
	(With 300 x 300 dpi 16 Half Tone layers)	
/linimum Ink Droplet Volume	3.8 pl	
Print Speed	Maximum print speed of 255sqm/h	Maximum print speed of 246sqm/h
Margin (Roll paper)	7 mm (Right / Left), 5 mm (top), 5 mm (Bott	om)
	(14 mm when using Media Holding Plates)	
nk		
nk Types	Dye Sublimation Transfer Ink	
nk Brand Name	UltraChrome DS	
Colours	Cyan, Magenta, Yellow, High Density Black	Cyan, Magenta, Yellow, High Density Black,
		Light Cyan, Light Magenta /
		Cyan, Magenta, Yellow, High Density Black,
		Fluorescent Pink, Fluorescent Yellow
nk Capacity	10,000 ml	
nk Case	Ink cartridge	
/ledia Handling		
Paper Path	Friction Feed	
Maximum Diameter / Weight	Max. diameter 250 mm / 60 Kg (Roll)	
	Max. diameter 250 mm / 60 Kg (Reel)	
Paper Width (Roll)	300 mm - 1,950 mm	
	(Take-up reel support over than 914.4 mm)	
Paper Thickness (Roll)	up to 1 mm	
Roll Paper Remaining	The remaining amount is managed on contr	rol panel.
Control Panel		
Colour/Size	9.0 inch Touch Panel	
Connectivity	ord more roading drief	
nterfaces	USB 3.0	
10.14000	1000Base-T	
Printer Language	ESC/P raster	
Memory	155GB	
Environmental Characteristics		
Temperature	Operating: 10°C - 35°C	
iemperature	Storage (before unpacking): -20°C - 60°C	
	1 month at 40°C, 120 hours at 60°C	
	Storage (after unpacking): -20°C - 40°C	
	1 month at 40°C	
Humidity	Operating: 20 - 80% (no condensation)	
	Storage: 5 - 85% (no condensation)	
Dimensions & Weight		
Printing Dimensions (W x H x D)	4,607 x 1,886 x 1,303 mm	5,008 x 1,886 x 1,303 mm
Storage Dimensions (W x H x D)	4,607 x 1,886 x 1,303 mm	5,008 x 1,886 x 1,303 mm
Veight	Approx. 736 kg (Without ink cartridges)	Approx. 767 kg (Without ink cartridges)
Electrical Specification		
/oltage	AC200-240V x 2	
Rated Current	16A x 2	
Power Consumption		
Operating	Approx. 3.9 kW	Approx. 4.4kw
Ready / Sleep	Approx. 221 W	Approx. 230W
Power Off (Stand by)	Approx. 9.6 W	
Acoustic Noize Level	7 lpprox. 5.5 **-	
Sound Pressure Level <db(a)></db(a)>	Approx. 59 dB	
Jtility Software	Арргох. Ээ ав	
Jtility Software Jtility Software (Bundled in CD)	Windows only:	Windows only:
Julity Cortware (Burluicu III CD)	CD: Epson Communication Driver,	Epson Communication Driver, Installer
	EpsonNet Print, EpsonNet Setup,	Package, Epson Software Updater, EpsonNet,
	EpsonNet Confi g SE, Epson Manual	PrintEpsonNet, SetupEpsonNet Confi g SE,
	Launcher, User's Guide (Excerpt),	Epson Manual Launcher, User's Guide
	Epson Software Updater, Installer Package	
	DVD: Epson Edge Print	
Jtility Software (Web delivery)	Windows and Mac:	Windows only:
	Epson Communication Driver, Online	Epson Communication Driver, EpsonNet
	Manual, Epson Video Manuals, User's	Print, EpsonNet Setup, LFP Accounting Tool
	Guide, Network Guide, User's Guide	Windows and Mac:
	(Excerpt), Start-Up Guide, Epson Manual	Epson Web Installer, Epson Software Updater,
	Launchern, Epson Control Dashboard,	EpsonNet Confi g SE, Epson Edge Dashboard,
	EpsonNet Setup, EpsonNet Confi g, EpsonNet Print, Software Updater, LFP	Epson Manual Launcher, Online Manual,
	EpsonNet Print, Software Updater, LFP Accounting Tool, Epson Control Dashboard	Epson Video Manuals, User's Guide (Excerpt),
System	Accounting Tool, Epson Control Dashboard	User's Guide, Network Guide, Start-Up Guide
Vin PC System Requirement	Macintosh Mac OS X(10.6.8 or later)	Windows PC System:
Will O Oystern riequilement	CPU: Core 2 Duo 2.0GHz	CPU: Intel Corei3 3.0GHz or faster
	Memory: Memory more than 1GB	(released after April 2014)
	HDD: Free space more than 500MB	Memory: Memory more than 8GB
	(For utility software, please refer to system	HDD (Free space during installation: 50GB
	requirement for each Utility software)	or more)
		Mac System Requirement:
		CPU: Multicore 3.0GHz
		Memory: Memory more than 4GB
		HDD: Free space more than 2GB

Dimensions & Weight

SC-F10030

Weight: 736 kg (Without ink cartridges)



SC-F10030H

Weight: 767 kg (Without ink cartridges)



C12C936041 Presser Rolle C13S210103 Cleaning Kit C13S210065 Wiper Roll
C13S210071 Waste Ink Bottle

C13T43G100	UltraChrome DS High Density Black Ink (10L)
C13T43G200	UltraChrome DS Cyan Ink (10L)
C13T43G300	UltraChrome DS Magenta Ink (10L)
C13T43G400	UltraChrome DS Yellow Ink (10L)
C13T43G500	UltraChrome DS Light Cyan Ink (10L)
C13T43G600	UltraChrome DS Light Magenta Ink (10L)
C13T43G700	UltraChrome DS Fluorescent Yellow Ink (10L)
C13T43G800	UltraChrome DS Fluorescent Pink Ink (10L)
C12C933881	Take Up Media Holder
C12C933901	Take In Media Holder
C12C936031	Media Cleaner Brush
C12C936041	Presser Roller Spacer



NEP 1902 Nissenken

Textile and leather chemicals.


Tested and verified.
www.oeko-tex.com/ecopassport

© 2024 Epson India Pvf. Ltd. All Rights Reserved.
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Dealer's Stamp





Warranty



Headquarter (India): DCC Print Vision LLP,

1 Year Self-Repair Warranty*

802, Kamla Executive Park, Opp. Vazir Glass Work, Off. M.V. Road, J.B. Nagar, Andheri (East), Mumbai- 400 059, India. Tel.: +91 022 4085 5000



+91 9930 200 400 🔀 salesinquiry@groupdcc.com 🌐 www.groupdcc.com



