

Roll To Roll Heat Transfer Machine



Introducing New

SPINE Pro 550

Powered By DCC



The cutting-edge technologies incorporated in the various manufacturing processes have resulted in increased efficiency and productivity. This continued upgradation through a constant focus on research and development has opened up a vista of exciting opportunities. The proven capacity of UNQ Transfer to deliver with precision and quality in a fast-paced work environment makes an association with this fast-rising company an opportunity to widen business possibilities.











Product Feature

- PLC Controlled machine.
- Vacuum sealed oil drum ensure zero damage.
- Easy and operator Friendly machine.
- Effective combination of work styles.
- Convenient removal/attachment and operation of attachments.
- Precise temperature control with digital type controller (HMI).
- Tension control for printing material in roll.
- Special motor enables strong torque at low speed.
- Actualworking length is indicated with digital on panel.
- Provision for UPS connection.
- Main drive rotation monitoring sensor.
- Air Supply Monitoring Switch.

Technical Specification

Content / Model	Sprint Pro 550 -1600	Sprint Pro 550 -1800	Sprint Pro 550 -2400	Sprint Pro 550 -3200
Working Width	1,600mm	1,800mm	2,400mm	3,200mm
Max Temperature	230°C	230°C	230°C	230°C
Installed Power	24.5kW	26kW	31.5kW	40kW
Max Current	34А (Ф3-415V)	37A (Ф3-415V)	44A (Φ3-415V)	56A (Ф3-415V)
Machine Size(mm)	W2,660 L2,350 H1,550	W2,860 L2,350 H1,550	W3,460 L2,350 H1,550	W4,260 L2,350 H1,550
Weight	2,090kg	2,240kg	2,500kg	3,050kg
Temperature Sensor	RTD PT100			
Certification	CE			

